Brand	Lexar®
Product Name Full	Lexar® Professional Workflow CFexpress™ 4.0 Type A Card Reader
Product Name Short	Workflow CFexpress™ 4.0 Type A Card Reader
Product Name E-commerce	Lexar® Professional Workflow CFexpress™ 4.0 Type A Card Reader, designed to pair with Lexar® Professional Workflow, USB-C cable/ USB-C to USB-A adapter, Compatible with PC Computers, Laptop, Tablet, Smartphone
Product Line	Consumer readers
Marketing Text 25-Word Description (<750 characters)	Made to pair with the Lexar® Professional Workflow dock, the Workflow CFexpress™ 4.0 Type A Card Reader supports speeds up to 40Gbps to maximize your workflow.
Marketing Text 50-Word Description (<750 characters)	Made to pair with the Lexar® Professional Workflow dock, the Workflow CFexpress™ 4.0 Type A Card Reader supports speeds up to 40Gbps to maximize your workflow and an aluminum finish that offers superior scratch resistance to weather heavy use even on location.
Bullet Feature 1	Supports new CFexpress 4.0 Type A cards with read speeds of up to 1800MB/s and write speeds of up to 1650MB/s[1] for maximized efficiency, and backwards-compatible with CFexpress 2.0 Type A cards
Bullet Feature 2	Specially crafted aluminum finish offers superior scratch resistance, making it great for on-location shoots
Bullet Feature 3	Compatible with Lexar Professional Workflow and Workflow Go which let you customize readers and portable SSDs for maximum efficiency
Bullet Feature 4	Includes a USB-C® to USB-C cable to easily connect with all your Type-C devices
Bullet Feature 5	Includes 3 years of worry-free warranty service
Footnote(s)/Disclaimer(s)	[1]Results may vary based on system configuration and card speed. Lexar is not liable for any loss of data or images. **[Product page only]** Product appearance, performance, software offerings, and packaging may vary depending on ship date and available inventory. Actual usable memory capacity may vary. 1GB equals 1 billion bytes.
Warranty	3-year
Market Segment	Consumer Electronics, Camera, Photo, Video
Category	reader, Workflow reader, docking station compatible reader
Sub Category	Type A card, USB Reader, USB 4, Lexar
Keywords for Search	CFexpress Type A card reader, Sony card reader, Workflow CFexpress reader module, Workflow CFexpress Type A reader module, CFexpress 4.0, CFexpress 4.0 reader, fastest CFexpress 4.0 Reader, Workflow for CFexpress 4.0, CFexpress 4.0 Type A Reader, CFexpress 4.0 Type A Workflow

Specifications	
Model	WF 730
Interface	USB 4

Operating Temperature	0° to 40°C (32°F to 104°F)
Storage Temperature	-20° to 85°C (-4°F to 185°F)
Dimensions (L x W x H)	103.4 x 57.7 x 12.0mm
Weight	84g
Systems Supported	Mac® OS 10.8+ Windows® 11/10/8/7/Vista/XP USB 2.0+ port
Shock	1500G, duration 0.5ms, Half Sine Wave
Vibration	10~2000Hz, 1.5mm, 20G, 1 Oct/min, 30min/axis (X,Y,Z)
Humidity	95%

Ordering Information

	Part Number	**Description**	**Single UPC**	**10-Pack UPC**
Single EAN and/ or Master Carton UPC (GLOBAL)	LPWF730N-5ANGL	Lexar Professional Workflow CFexpress4.0 Type A card reader	843367136179	10843367136176

Country of Origin	China
Harmonized Tariff Schedule	8471.80.9000
Compliance	FCC, CE, C-TICK, VCCI, RoHS, VCCI, KC, WEEE

Weights and Dimensions		
Product		
Unit Weight	0.185 lbs	84 g
Unit Dimensions (L x W x H)	4.07'' x 2.27'' x 0.47''	103.4mm x 57.7mm x 12.0mm
Image		

Retail Box – Master Pack (All Regions)		
Package Type	Retail box	
Qty Per Package	1	
Shipping Weight	0.327 lbs	148.2 g

Package Dimensions (L x W x H)	5.91'' x 3.93'' x 1.37''	150mm x 100mm x 35mm
Image		
Retail Box – Inner Carton (All Regions)		
Package Type	Inner box	
Qty Per Package	10	
Shipping Weight		
Package Dimensions (L x W x H)	10.31'' x 7.67'' x 4.68''	262mm x 195mm x 119mm
Retail Box – Master Carton (All Regions)		
Package Type	Master pack	
Qty Per Package	40	
Shipping Weight		
Package Dimensions (L x W x H)	16.14'' x 10.91'' x 10.63''	410mm x 277mm x 270mm