ELEMENTS	Fixed-charge back plate, permanently polarized condenser
POLAR PATTERNS	Line-cardioid, Figure-of-eight
FREQUENCY RESPONSE	30-20,000 Hz
LOW FREQUENCY ROLL-OFF	80 Hz, 12 dB/octave
OPEN CIRCUIT SENSITIVITY	Mid: -30 dB (31.6 mV) re 1V at 1 Pa; Side: -34 dB (19.9 mV) re 1V at 1 Pa; LR Stereo: -36 dB (15.8 mV) re 1V at 1 Pa
IMPEDANCE	200 ohms
MAXIMUM INPUT SOUND LEVEL	Mid: 123 dB SPL, 1 kHz at 1% T.H.D.; Side: 127 dB SPL, 1 kHz at 1% T.H.D.; LR Stereo: 126 dB SPL, 1 kHz at 1% T.H.D.
DYNAMIC RANGE (typical)	Mid: 101 dB, 1 kHz at Max SPL; Side: 101 dB, 1 kHz at Max SPL; LR Stereo: 102 dB, 1 kHz at Max SPL
SIGNAL-TO-NOISE RATIO	Mid: 72 dB SPL, 1 kHz at 1 Pa; Side: 68 dB SPL, 1 kHz at 1 Pa; LR Stereo: 70 dB SPL, 1 kHz at 1 Pa
PHANTOM POWER REQUIREMENTS	11-52V DC, 4 mA typical at 48V, each channel
SWITCHES	M-S, LR Stereo-Wide (LR-W), LR Stereo-Narrow (LR-N); Flat, roll-off
WEIGHT	142 g (5.0 oz)
DIMENSIONS	380.0 mm (14.96") long, 21.0 mm (0.83") diameter
OUTPUT CONNECTOR	Integral XLR5M-type
CABLE	Dual 0.61 m (24") shielded two-conductor, terminated in two XLR3M-type connectors
ACCESSORIES FURNISHED	AT8405a stand clamp for 5/8"-27 threaded stands; AT8135 foam windscreen; 5/8"-27 to 3/8"-16 threaded adapter; protective carrying case