Thank you for choosing Magnus.

DuraPod BX Mini Tripod Components



Precautions

- Please ensure that all knobs, handles, and legs are secured properly before mounting your camera on this tripod.
- Never transport, carry, or store this tripod while your camera is attached.
- Do not use solvents, grease, or oil on any of the tripod components. Use only a mild soap solution to clean, and wipe dry with a lint-free cloth.
- Do not exceed the maximum load capacity.
- All images are for illustrative purposes only.

ONE-YEAR LIMITED WARRANTY

This Magnus product is warranted to the original purchaser to be free from defects in materials and workmanship under normal consumer use for a period of one (1) year from the original purchase date or thirty (30) days after replacement, whichever occurs later. The warranty provider's responsibility with respect to this limited warranty shall be limited solely to repair or replacement, at the provider's discretion, of any product that fails during normal use of this product in its intended manner and in its intended environment. Inoperability of the product or part(s) shall be determined by the warranty provider. If the product has been discontinued, the warranty provider reserves the right to replace it with a model of equivalent quality and function.

This warranty does not cover damage or defect caused by misuse, neglect, accident, alteration, abuse, improper installation or maintenance. EXCEPT AS PROVIDED HEREIN, THE WARRANTY PROVIDER MAKES NEITHER ANY EXPRESS WARRANTIES NOR ANY IMPLIED WARRANTIES, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. This warranty provides you with specific legal rights, and you may also have additional rights that vary from state to state.

To obtain warranty coverage, contact the Magnus Customer Service Department to obtain a return merchandise authorization ("RMA") number, and return the defective product to Magnus along with the RMA number and proof of purchase. Shipment of the defective product is at the purchaser's own risk and expense.

For more information or to arrange service, visit www.magnustripods.com or call Customer Service at 212-594-2353.

Product warranty provided by the Gradus Group. www.gradusgroup.com
MAGNUS is a registered trademark of the Gradus Group. © 2016 Gradus Group LLC. All Rights Reserved.

MAGNUS™ A Gradus Group Brand

Make A Better Picture™

www.magnustripods.com

GG1

MAGNUS™



mini series

TM-11B

DuraPod BX

Mini Tripod

Owner's Manual



Extending the Tripod Legs

1. Spread the tripod legs.
2. Rotate the twist locks a quarter turn counterclockwise to loosen them. *(Fig. A)*
3. Pull out the legs to their full extension. *(Fig. B)*
4. Rotate the twist locks clockwise until secure.



Figure A



Figure B

Collapsing the Tripod Legs

1. Rotate the twist locks a quarter turn counterclockwise to loosen them. *(Fig. C)*
2. Give each leg a firm push to fully collapse it. *(Fig. D)*
3. Rotate the twist locks clockwise until secure.
4. Fold the legs in.



Figure C



Figure D

Using the Universal Ball Head

- To position the ball head, loosen the ball head Locking Knob by rotating it counterclockwise. Position the ball head as required, and tighten ball head locking knob by rotating it clockwise. *(Fig. E)*
- To change the camera orientation from horizontal to vertical position, loosen the ball head locking knob. Rotate the ball head 90˚ in either direction, and tighten the ball head locking knob. *(Fig. F)*



Figure E



Figure F

Adjusting the Center Column

1. To raise or lower the center column, loosen the center column locking collar by rotating it counterclockwise. *(Fig. G)*
2. Position the center column at the desired height, and tighten the locking collar by rotating it clockwise. *(Fig. H)*



Figure G



Figure H

Using the Suction Cup

1. Start with the tripod legs collapsed but in spread position.
2. Loosen the center column locking collar, and push the center column downward until the suction cup adheres to the surface. *(Fig. I)*
3. Tighten the center column locking collar.

Note: For an enhanced grip, slightly moisten the bottom of the suction cup.



Figure I